

# Negative optical refractive index resulting from a moving regular medium

Jian Qi Shen<sup>1,2</sup>

<sup>1</sup> Centre for Optical and Electromagnetic Research, State Key Laboratory of Modern Optical Instrumentation, Zhejiang University, Hangzhou Yuquan 310027, P.R. China

<sup>2</sup> Zhejiang Institute of Modern Physics and Department of Physics, Zhejiang University, Hangzhou 310027, P.R. China  
(February 2, 2008)

The optical refractive index of a moving regular medium is calculated by using the Lorentz transformation in this note. It is shown that in some velocity region of medium moving relative to the initial frame K, the moving medium may possess a negative index of refraction measured by the observer fixed at the frame of reference K.

**PACS numbers:** 78.20.Ci, 03.50.De

More recently, a class of artificial composite meta-materials (termed “left-handed media”), which possess the *negative* indices of optical refraction, attract extensive attention in various areas such as applied electromagnetism, classical optics, materials science as well as condensed matter physics [1–8]. Pendry *et al.* suggested that such left-handed materials can be designed and fabricated by using both the *array of long metallic wires* (ALMWs) [9] and the *split ring resonators* (SRRs) [10,11]. A combination of the two structures yields a left-handed medium. Apart from such artificial fabrications, does there exist another alternative to the negative index of refraction? In this note, I will demonstrate that a moving regular medium with a velocity in a suitable region (associated with its rest refractive index  $n$ )<sup>1</sup> possesses a negative index of refraction, which may be a physically interesting effect and might deserve further discussion.

Suppose we have a regular anisotropic medium with the rest refractive index tensor  $\hat{n}$ , which is moving relative to an inertial frame K with speed  $\mathbf{v}$  in the arbitrary directions. The rest refractive index tensor  $\hat{n}$  can be written as  $\hat{n} = \text{diag}[n_1, n_2, n_3]$  with  $n_i > 0, i = 1, 2, 3$ . Thus the wave vector of a propagating electromagnetic wave with the frequency  $\omega$  reads  $\mathbf{k} = \frac{\omega}{c}(n_1, n_2, n_3)$  measured by the observer fixed at this medium. In this sense, one can define a 3-D vector  $\mathbf{n} = (n_1, n_2, n_3)$ , and the wave vector  $\mathbf{k}$  may be rewritten as  $\mathbf{k} = \mathbf{n} \frac{\omega}{c}$ . Now we analyze the phase  $\omega t - \mathbf{k} \cdot \mathbf{x}$  of the above time-harmonic electromagnetic wave under the following Lorentz transformation

tion

$$\mathbf{x}' = \gamma(\mathbf{x} - \mathbf{v}t), \quad t' = \gamma\left(t - \frac{\mathbf{v} \cdot \mathbf{x}}{c^2}\right), \quad (1)$$

where  $(\mathbf{x}', t')$  and  $(\mathbf{x}, t)$  respectively denote the spacetime coordinates of the initial frame K and the system of moving medium, the spatial origins of which coincide when  $t = t' = 0$ . Here the relativistic factor  $\gamma = \left(1 - \frac{v^2}{c^2}\right)^{-\frac{1}{2}}$ . Thus by using the transformation (1), the phase  $\omega t - \mathbf{k} \cdot \mathbf{x}$  observed inside the moving medium may be rewritten as the following form by using the spacetime coordinates of K

$$\omega t - \mathbf{k} \cdot \mathbf{x} = \gamma\omega\left(1 - \frac{\mathbf{n} \cdot \mathbf{v}}{c}\right)t' - \gamma\omega\left(\frac{\mathbf{n}}{c} - \frac{\mathbf{v}}{c^2}\right) \cdot \mathbf{x}', \quad (2)$$

the term on the right-handed side of which is just the expression for the wave phase in the initial frame K. Hence, the frequency  $\omega'$  and the wave vector  $\mathbf{k}'$  of the observed wave we measure in the initial frame K are given

$$\omega' = \gamma\omega\left(1 - \frac{\mathbf{n} \cdot \mathbf{v}}{c}\right), \quad \mathbf{k}' = \gamma\omega\left(\frac{\mathbf{n}}{c} - \frac{\mathbf{v}}{c^2}\right), \quad (3)$$

respectively.

To gain some insight into the meanings of the expression (3), let us consider the special case of a boost (of the Lorentz transformation (1)) in the  $\hat{x}_1$ -direction, in which the medium velocity relative to K along the positive  $\hat{x}_1$ -direction is  $v$ . In the meanwhile, we assume that the wave vector of the electromagnetic wave is also parallel to the positive  $\hat{x}_1$ -direction. If the *rest* refractive index of the medium in the  $\hat{x}_1$ -direction is  $n$ , its (moving) refractive index in the same direction measured by the observer fixed at the initial frame K is of the form

$$n' = \frac{ck'}{\omega'} = \frac{n - \frac{v}{c}}{1 - \frac{nv}{c}}, \quad (4)$$

which is a relativistic formula for the addition of “refractive indices” ( $-\frac{v}{c}$  provides an effective index of refraction).

Note that here  $n'$  observed in the frame K may be negative. If, for example, when  $n > 1$ , the medium moves at

$$c > v > \frac{c}{n} \quad (5)$$

(and in consequence,  $k' > 0, \omega' < 0$ ); or when  $0 < n < 1$ , the medium velocity with respect to K satisfies

<sup>1</sup>The rest refractive index is just the one measured by the observer fixed at the regular/ordinary medium. In what follows, we will derive the relativistic transformation for the optical refractive index (tensor) of a moving medium.

$$c > v > nc \quad (6)$$

(and consequently,  $k' < 0$ ,  $\omega' > 0$ ), then  $n'$  is negative. The former case where  $k' > 0$ ,  $\omega' < 0$  is of physical interest. In the paper [8], it was shown that the photon in the negative refractive index medium behaves like its *anti-particle*, which, therefore, implies that we can describe the wave propagation in both left- and right-handed media in a unified way by using a complex vector field [8].

In the above, even though we have shown that in some certain velocity regions, the moving medium possesses a negative  $n'$ , such a moving medium cannot be surely viewed as a left-handed medium. For this point, it is necessary to take into account the problem as to whether the vector  $\mathbf{k}$ , the electric field  $\mathbf{E}$  and the magnetic field  $\mathbf{H}$  of the electromagnetic wave form a left-handed system or not<sup>2</sup>. For simplicity and without the loss of generality, we choose the electric and magnetic fields of the electromagnetic wave in the medium system as

$$\mathbf{E} = (0, E_2, 0), \quad \mathbf{B} = (0, 0, B_3). \quad (7)$$

In the regular medium (right-handed medium with  $n > 0$ ), the wave vector (along the positive  $\hat{x}_1$ -direction with the modulus  $k$ ) and such  $\mathbf{E}$  and  $\mathbf{B}$  (or  $\mathbf{H}$ ) form a right-handed system<sup>3</sup>. In the frame of reference K, according to the Lorentz transformation, one can arrive at

$$E'_2 = \gamma(E_2 - vB_3) \quad B'_3 = \gamma\left(B_3 - \frac{v}{c^2}E_2\right). \quad (8)$$

For convenience, here we will think of the medium as an isotropic one, *i.e.*, the refractive index  $n'$ , permittivity  $\epsilon'$  and the permeability  $\mu'$  of the moving medium are all the scalars rather than the tensors. First we consider the case of Eq.(6) where  $k' < 0$ ,  $\omega' > 0$ . In order to let the moving medium with a negative index of refraction be a real left-handed one, the wave vector ( $k' < 0$ ),  $E'_2$  and  $H'_3$  of the electromagnetic wave measured in K should form a left-handed system. Because of  $k' < 0$  and  $B'_3 = \mu'\mu_0 H'_3$  with  $\mu_0$  being the magnetic permeability in a vacuum, if  $\mu'$  is negative<sup>4</sup>, then only the case of  $E'_2 < 0$  and  $B'_3 > 0$  (and vice versa) will lead to the left-handed system<sup>5</sup> formed

<sup>2</sup>This requirement is the standard definition of a left-handed medium. Apparently, it is seen that the two concepts *left-handed medium* and *negative refractive index medium* is not completely equivalent to each other.

<sup>3</sup>Thus if  $E_2 > 0$  is chosen to be positive, then  $B_3$  is also positive. In what follows, we will adopt this case (*i.e.*,  $E_2 > 0$  and  $B_3 > 0$ ) without the loss of generality.

<sup>4</sup>In the left-handed medium, the electric permittivity and the magnetic permeability are simultaneously negative.

<sup>5</sup>Since  $k' < 0$ , in order to form a left-handed system, the signs of  $E'_2$  and  $H'_3$  should not be opposite to each other. So, the signs of  $E'_2$  and  $B'_3$  should be opposite due to  $\mu' < 0$ .

by the wave vector ( $k' < 0$ ),  $E'_2$  and  $H'_3$ . So, it follows from Eq.(8) that when the medium velocity relative to K is in the range

$$\frac{c^2 B_3}{E_2} < v < \frac{E_2}{B_3} \quad (\text{if } E_2^2 > c^2 B_3^2), \quad (9)$$

or

$$\frac{c^2 B_3}{E_2} > v > \frac{E_2}{B_3} \quad (\text{if } E_2^2 < c^2 B_3^2), \quad (10)$$

then the wave vector, electric field and magnetic field measured in K will truly form a left-handed system.

In conclusion, if the medium velocity satisfies both Eq.(6) and Eq.(9) or (10), then the moving medium will be a left-handed one observed from the observer fixed in the initial frame K.

As far as the case of Eq.(5) where  $k' > 0$ ,  $\omega' < 0$  is concerned, it is also possible for the moving material to become a left-handed medium. But the case of  $\omega' < 0$  has no the practical counterpart (at least in the real situation where the artificial composite materials is designed). So, we would not further discuss the case of  $\omega' < 0$ .

Although the subject of the present note seems to be somewhat trivial, it is helpful for understanding the properties of wave propagation (such as causality problem, the problem of energy propagating outwards and backwards from source [12], *etc.*) in the left-handed medium.

**Acknowledgements** This work was supported partially by the National Natural Science Foundation of China under Project No. 90101024.

- 
- [1] D.R. Smith, W.J. Padilla, D.C. Vieret *al.*, Phys. Rev. Lett. 84 (2000) 4184; R.A. Shelby, D.R. Smith, and S. Schultz, Science 292 (2001) 77.
  - [2] V.V. Klimov, Opt. Comm. 211 (2002) 183.
  - [3] R.W. Ziolkowski, Phys. Rev. E 64 (2001) 056625.
  - [4] J.A. Kong, B.L. Wu, and Y. Zhang, Appl. Phys. Lett. 80 (2002) 2084; N. Garcia and M. Nieto-Vesperinas, Opt. Lett. 27 (2002) 885.
  - [5] J.B. Pendry, Phys. Rev. Lett. 85 (2001) 3966.
  - [6] Z.M. Zhang, C.J. Fu, Appl. Phys. Lett. 80 (2002) 1097.
  - [7] J.Q. Shen, Phys. Scr. 68 (2003) 87.
  - [8] J.Q. Shen, cond-mat/0308349 (2003).
  - [9] J.B. Pendry, A.J. Holden, D.J. Robbins, and W.J. Stewart, J. Phys. Condens. Matter 10 (1998) 4785.
  - [10] J.B. Pendry, A.J. Holden, W.J. Stewart, and I. Youngs, Phys. Rev. Lett. 76 (1996) 4773; J.B. Pendry, A.J. Holden, D.J. Robbins, and W.J. Stewart, IEEE Trans. Microwave Theory Tech. 47 (1999) 2075.
  - [11] S.I. Maslovski, S.A. Tretyakov, and P.A. Belov, Inc. Microwave Opt. Tech. Lett. 35 (2001) 47.
  - [12] D.R. Smith and N. Kroll, Phys. Rev. Lett. 85 (2000) 2933.